

## CONSTRUCTION PRODUCTS REGULATION 2011 DECLARATION OF PERFORMANCE

**DoP Number:** 

1. Unique identification code of the product-type:

certificate of constancy of performance of the product.

8. European Technical Assessment:

N/A

AR717 Series 5 Lever Mortice Deadlock

HUK0048

| 2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:        |
|---|
| AR717 Series 5 Lever Mortice Deadlock   |
| 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: |
| For use on fire and smoke compartmentation doors, when fitted in accordance with the manufacturer's fitting instructions.                                   |
| 4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):                            |
| ARRONE HOPPE (UK) Ltd, Gailey Park, Gravelly Way, Standeford, West Midlands Wolverhampton, WV10 7GW, United Kingdom   |
| 5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):                   |
| N/A   |
| 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:                     |
| System 1  |

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard.

EN 12209: 2003 incorporating Corrigendum N° 1 Notified product certification body No. 1121 performed the determination of the product type on the basis of type testing (including sampling); initial inspection of the manufacturing plant and of the factory production control and continuous surveillance; assessment and evaluation of factory production control; and issued the

## 9. Declared performance

| Essential characteristic Self closing  | Performance   | Harmonised technical specification                  |
|--|---|---|
| 5.4.2 Closing force  | Grade 8, Up to 200 kg door mass, 15 N max. closing force  | EN 12209: 2003<br>incorporating<br>Corrigendum N° 1 |
| 5.1.2 Re-latching force of latch bolt  | Deadlock – N/A  |   |
| Essential characteristic<br>Durability of self closing                                       | Performance   | Harmonised technical specification                  |
| 5.3.1 Durability of latch action   | Deadlock – N/A  | EN 12209:2003<br>incorporating<br>Corrigendum N° 1  |
| Ability to maintain the door in the closed position and not contribute to the spread of fire | Grade 1   |   |
| Dangerous Substances Annex ZA3   | The materials in the product(s) do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations. |   |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Mr Neil Morgan

Commercial Director

Date of issue: 30/06/2013

HOPPE (UK) Ltd

Standeford, West Midlands Wolverhampton, WV10 7GW

United Kingdom

This Declaration of Performance is issued on a standard template provided by the GAI for use in the door and hardware industries. There is no implied endorsement of the content, which is the responsibility of the issuing company.



The Guild of Architectural Ironmongers

BPF House, 6 Bath Place, Rivington Street, London, EC2A 3JE

Tel: +44 (0) 20 7033 2480 | Fax: +44 (0) 20 7033 2486